

SharePoint Update List Item Activity Overview

Last Modified on 03/12/2018 7:18 am EDT

Context

Use the SharePoint Update List Item Activity to update an item from a SharePoint library as part of a dynamic workflow.

Wizard Tips

- You can define most activity parameters by selecting if from a data source, entering the value manually, or making it the result of an expression.
- All field names in the SharePoint activity binding screens must be the SharePoint internal name.

Bindings

Update List Item Bindings ?

Request

- UpdateListItem
 - ListReference list
 - Guid Id = New Guid((Demo Settings).Query("DemoSettings")["List
 - ListItem listItem
 - int Id = (UploadDocumentActivity1).ReturnValue
 - FieldValues FieldValues
 - FieldValue_0
 - string Name = (Demo Settings).Query("DemoSettings")["C
 - Object Value = "** Updated at " + ToString(Now())
 - FieldValue_1
 - string Name = (Demo Settings).Query("DemoSettings")["L
 - Object Value = "** Updated by " + rt.CurrentUser.UserNam

General

(Name) UpdateListItem

Security

Credential Type Store

Credential Name ST_SharePoint_User

Misc

Site URL

Show bound members only

Back Finish Cancel

Binding	Description
list	<p>Click this field, and then on the right side select the Type.</p> <ul style="list-style-type: none">• ListByTitleReference: select the list by its title.• ListByIdReference: select the list by its ID. <p>(Optional) define the list value by selecting it from a DataSource or entering the value manually or clicking the ellipsis button to set it as the result of an expression.</p>

Binding	Description
Title/Id	Enter the list Title/Id or click the ellipsis button to set it as the result of an expression.
ListItemFields	You can define the list item fields by selecting it from a DataSource or entering the Value manually or clicking the ellipsis button to set it as the result of an expression.
FieldValues	Here you can define a set of fields for the list item. For each field, define the name and value by entering their Value manually or clicking the ellipsis button to set it as the result of an expression.
(Name)	The name of the activity.
Credential Type	<ul style="list-style-type: none"> • None • Application • Impersonated • Store
Credential Name	Click the ellipsis button to select the Credential Name.
Site URL	(Optional) Enter an expression for the site URL. This will allow you to dynamically determine the target site during execution. The credentials must be valid for the calculated site.
Show bound members only	Show only bound members in the above fields.