

Add a Custom Column on a Webpart

Last Modified on 08/03/2017 7:35 am EDT

Learn how to add a custom column to a Cora SeQUENCE webpart.

In the *Template* property, you specify the HTML that is rendered in the column. You can write JavaScript code between # signs, and the *data* variable contains the row's data. You can reference any column that is defined in the `ServiceMetadata` file, and also variables that are propagated to the webpart.

Procedure

1. Navigate to `C:\Program Files\PNMsoft\Shared Resources\Components\Flowtime\Config\ServiceMetadata`.
2. Locate the config file for the webpart that you want to add a column to.
3. Copy and rename the config file.
For example, add the word custom to the file name: `MessagesServiceMetadata.config` to `MessagesServiceMetadataCustom.config`.
4. In the custom config file, add a section similar to the following example.

```
<code></code>
```
5. Navigate to `C:\Program Files\PNMsoft\Shared Resources\Components\Flowtime\Config`, and copy the `Services.config` file
6. Rename the file to `Services.Custom.config`, and save it in `C:\Program Files\PNMsoft\Shared Resources\Components\Flowtime\Config\ServiceMetadata`.
7. In the `Services.Custom.config` file, in the `ServiceMetatdata` section of the webpart that you want to add the column to, change the path to the new Service Metadata config file you created. In our example, `ServiceMetadata="~/shared resources/Components/Flowtime/config/ServiceMetadata/MessagesServiceMetadataCustom.config`