

# ProcessTOGO Windows Authentication

Last Modified on 07/01/2019 10:57 am EDT

By default, Process<sup>TOGO</sup> is configured with forms authentication. Follow this procedure to configure Process<sup>TOGO</sup> with Windows authentication.

## Procedure

1. Access the Internet Information System manager (IIS) on the machine that hosts the copy of Process<sup>TOGO</sup>.
2. Configure the necessary settings for the Process<sup>TOGO</sup> application.
  - a. Open **Authentication Settings** and enable **Windows Authentication**.
  - b. Configure authentication settings in the features view for the `default.aspx` file.  
The `default.aspx` file is in the Process<sup>TOGO</sup> root folder
    - i. Enable **Windows Authentication**.
    - ii. Disable **Anonymous Authentication**.
3. In IIS, on the Process<sup>TOGO</sup> application, open the features for the `default.aspx` file, which is on the root folder of Process<sup>TOGO</sup>, and enable **Windows Authentication** and disable **Anonymous Authentication**.
4. Edit the Process<sup>TOGO</sup> `web.config` file, as necessary.
  - a. In the section, under the authentication section, make sure you have the `WindowsAuthenticationProvider` as the only provider, remove or comment out any others.
  - b. Set the `forms authentication to enabled` argument to **false**.

5.

6. Verify that the location for the `default.aspx` file matches the location detailed in this step. Add the `default.aspx` file location if it is not in the `web.config` file.

7. Verify that the location for the `WindowsLogout.aspx` file matches the location detailed in this step. Add the `WindowsLogout.aspx` file location if it is not in the `web.config` file.