

PowerShell Function: Install-CoraSeQuenceSite

Last Modified on 01/12/2021 12:27 pm EST

V9.6

Method

CoraSeQuence.Sites

Description

Installs, reinstalls, and upgrades a Cora SeQuence site.

Syntax

```
Install-CoraSeQuenceSite [-SourcePath] [[-ServiceAccount] ] [[-DestinationPath] ] [-SiteType] [[-SiteID] ] []
```

Parameters

-SourcePath

The full local path to the application package.

Required?	true
Position?	1
Default value	
Accept pipeline input?	false
Accept wildcard characters ?	false

-ServiceAccount

The credentials to be used as the Application Pool identity.

Required?	false
Position?	2
Default value	
Accept pipeline input?	false
Accept wildcard characters	false

?

-DestinationPath

The path where the site files are installed. If not provided, the Cora SeQuence default location is used:

```
C:\inetpub\wwwroot\Cora SeQuence\[Site]
```

If the path is provided, but the site already exists, for example in upgrade scenarios, the new path is ignored, and the current site location is used.

Required?	false
Position?	3
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-SiteType

Determines which Cora SeQuence site is deployed by the package: Flowtime or Administration.

Required?	true
Position?	4
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-SiteID

Sets the numeric ID of the site instance.

Required?	false
Position?	5

Default value	1
Accept pipeline input?	false
Accept wildcard characters?	false

This function supports these common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable.

For more information, see [about_CommonParameters](#).

Example

```
PS C:\>Install-CoraSeQuenceSite -SourcePath "C:\Flowtime.zip" -SiteType Flowtime
```

V9.0

Method

CoraSeQuence.Sites

Description

Installs, reinstalls, and upgrades a Cora SeQuence site.

Syntax

```
Install-CoraSeQuenceSite [-SourcePath] [[-ServiceAccount] ] [[-DestinationPath] ] [-SiteType] []
```

Parameters

-SourcePath

The full local path to the application package.

Required?	true
Position?	1
Default value	
Accept pipeline input?	false
Accept wildcard character	false

s?

-ServiceAccount

The credentials to be used as the Application Pool identity.

Required?	true
Position?	2
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-DestinationPath

The path where the site files are installed. If not provided, the Cora SeQuence default location is used:

```
C:\inetpub\wwwroot\Cora SeQuence\[Site]
```

If the path is provided, but the site already exists, for example in upgrade scenarios, the new path is ignored, and the current site location is used.

Required?	true
Position?	3
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-SiteType

Determines which Cora SeQuence site is deployed by the package: Flowtime or Administration.

Required?	true
Position?	1
Default value	
Accept pipeline input?	false

Accept wildcard characters?	false
------------------------------------	--------------

This function supports these common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable.

For more information, see [about_CommonParameters](#).

Example

```
PS C:\>Install-CoraSeQuenceSite -SourcePath "C:\Flowtime.zip" -SiteType Flowtime
```