

# PowerShell Function: New-CoraSeSequenceDeploymentPackage

Last Modified on 01/12/2021 12:28 pm EST

V9.6

Module

CoraSeQuence

## Description

Creates a Cora SeQuence deployment package.

The file name of the package is ""\_""\_""\_Deployment.zip"

## Syntax

```
New-CoraSeSequenceDeploymentPackage [-BuildOutputPath] [-DestinationPath] [[-ApplicationPackageFileName] ] [[-DeploymentPackageFileName] ] []
```

## Parameters

### -BuildOutputPath

The full path to the build output of the Cora SeQuence application.

Required?	true
Position?	1
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

### -DestinationPath

The full path to the folder where the deployment package should be created.

#### NOTE

If the directory exists, it must be empty.

Required?	true
Position?	2
Default value	

Accept pipeline input?	false
Accept wildcard characters?	false

### **-ApplicationPackageFileName**

The file name to be set for the application package, without the extension. If not provided, it is set to **"ApplicationType>"\_"++".zip"**.

Required?	false
Position?	3
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

### **-DeploymentPackageFileName**

The file name to be set for the deployment package, without the extension. If not provided, it is set to **"ApplicationType>"\_"++"\_Deployment.zip"**.

Required?	false
Position?	4
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

This function supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable.

For more information, see [about\\_CommonParameters](#).

## Examples

Example 1

```
PS C:\>New-CoraSeQuenceDeploymentPackage -BuildOutputPath "C:\Projects\Administration" -DestinationPath "D:\DeploymentPackages"
```

## Example 2

```
PS C:\>New-CoraSeQuenceDeploymentPackage -BuildOutputPath "C:\Projects\Flowtime" -DestinationPath "\\myserver\DeploymentPackages"
```

## V9.0

### Module

### CoraSeQuence

### Description

Creates a Cora SeQuence deployment package.  
The file name of the package is ""\_""\_""\_Deployment.zip"

### Syntax

```
New-CoraSeQuenceDeploymentPackage [-BuildOutputPath] [-DestinationPath] []
```

### Parameters

#### **-BuildOutputPath**

The full path to the build output of the Cora SeQuence application.

Required?	true
Position?	1
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

#### **-DestinationPath**

The full path to the folder where the deployment package should be created.

#### **NOTE**

If the directory exists, it must be empty.

Required?	true
Position?	2
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

This function supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable.

For more information, see [about\\_CommonParameters](#).

## Examples

### Example 1

```
PS C:\>New-CoraSeQuenceDeploymentPackage -BuildOutputPath "C:\Projects\Administration" -DestinationPath "D:\DeploymentPackages"
```

### Example 2

```
PS C:\>New-CoraSeQuenceDeploymentPackage -BuildOutputPath "C:\Projects\Flowtime" -DestinationPath "\\myserver\DeploymentPackages"
```