

Post-Deployment Procedures

Last Modified on 10/28/2020 2:30 am EDT

V9.x

Post-deployment V9.5

After you deploy Cora SeQuence V9.5, the new Email Listener activities use the new system tables tblEmailListenerMessages and tblEmailListenerMessagesAttachments, and the existing Email Listener activities continue to use their UACT tables. You can run the Email Listener post deployment script to configure all existing Email Listener activities to work with new tables. This improves performance, maintenance, and data usage in your workflows.

NOTE

This action is irreversible.

This change might break your solution, make sure to perform impact analysis prior to running the script.

Post-deployment V9.0

After you deploy Cora SeQuence V9.0 for the first time, you need to set up the Active Directory Synchronization Service and add the Windows service user to your organization's list of employees.

Configure Active Directory Synchronization Service (ADSS)

For information on how to configure ADSS, see [this article](#).

Add the Windows service user to the Employees table

To enable Background Runtime Service (BRS) functionality, such as sending emails and automatic link redirections, the Windows service user needs to be part of your organization's employee list.

You can set up a new user or use one of the existing Windows built-in accounts. If you use one of the built-in accounts, when you set up the Cora SeQuence user, enter the following parameters:

Built-in account	User name	Domain
Local System	SYSTEM	NT AUTHORITY
Local Service	LOCAL SERVICE	NT AUTHORITY
Network Service	NETWORK SERVICE	NT AUTHORITY

The Job Execution Service (JES) also needs to be a valid user in your organization's employee list.

It is recommended that BRS and JES use the same user account.

NOTE

If your employees are synced from the Active Directory, skip this procedure.

Procedure

1. Open the Administration site.
2. Go to **Administration > Organization Settings > Employees**.
3. Click **Add new record**.
4. Fill in the user details as shown in the following example:

Add Employee ?

First Name *	<input type="text" value="SeQ_svc"/>	E-mail	<input type="text"/>
Last Name *	<input type="text" value="BRS user"/>	Calendar	<input type="text" value="General"/>
Title	<input type="text" value="Employee"/>	Interface Language	<input type="text" value="English (USA)"/>
Domain	<input type="text" value="myDomain"/>	User Name *	<input type="text" value="SeQ_svc"/>
Time Zone	<input type="text" value="Default Time Zone"/>	Password	<input type="text"/>
<input checked="" type="checkbox"/> Active		Confirm Password	<input type="text"/>
		<input type="checkbox"/> Global Administrator	

5. Click **Add**.