

# PowerShell Function: Set-CoraSeQUENCEQuickSearchConfiguration

Last Modified on 01/12/2021 12:32 pm EST

V9.6

Module

CoraSeQUENCE

## Description

Configures the Cora SeQUENCE Hot Operations case search capability.

## Syntax

To enable the search feature:

```
Set-CoraSeQUENCEQuickSearchConfiguration [-Enable] [-PageSize ] [-SiteID ] []
```

To disable the search feature:

```
Set-CoraSeQUENCEQuickSearchConfiguration [-Disable] [-SiteID ] []
```

## Parameters

### -Enable []

Enables the case search capability.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

### -PageSize

Defines the number of results to display for search queries.

This parameter can be used with the `Enable` parameter or on its own.

Required?	false
Position?	named

Default value	0
Accept pipeline input?	false
Accept wildcard characters?	false

### **-Disable**

Disables the case search capability.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

### **-SiteID**

Sets the numeric ID of the site instance (for multiple instances of the same site).

Required?	false
Position?	named
Default value	1
Accept pipeline input?	false
Accept wildcard characters?	false

This function supports these common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable.

For more information, see [about\\_CommonParameters](#).

### Examples

To enable search, use only the `Enable` parameter. If you want to limit the number of retrieved results, add the `PageSize` parameter.

```
PS C:\>Set-CoraSeQuenceQuickSearchConfiguration -Enable -PageSize 100
```

To disable search, use only the `Disable` parameter.

```
PS C:\>Set-CoraSeQuenceQuickSearchConfiguration -Disable
```

## V9.2

### Module

### CoraSeQuence

### Description

Configures the Cora SeQuence Hot Operations case search capability.

### Syntax

To enable the search feature:

```
Set-CoraSeQuenceQuickSearchConfiguration [-Enable] [-PageSize ] []
```

To disable the search feature:

```
Set-CoraSeQuenceQuickSearchConfiguration [-Disable] []
```

### Parameters

#### **-Enable []**

Enables the case search capability.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

#### **-PageSize**

Defines the number of results to display for search queries.  
This parameter can be used with the `Enable` parameter or on its own.

Required?	false
-----------	-------

Position?	named
Default value	0
Accept pipeline input?	false
Accept wildcard characters?	false

### **-Disable** []

Disables the case search capability.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

This function supports these common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable.

For more information, see [about\\_CommonParameters](#).

### Examples

To enable search, use only the `Enable` parameter. If you want to limit the number of retrieved results, add the `PageSize` parameter.

```
PS C:\>Set-CoraSeQuenceQuickSearchConfiguration -Enable -PageSize 100
```

To disable search, use only the `Disable` parameter.

```
PS C:\>Set-CoraSeQuenceQuickSearchConfiguration -Disable
```