

# PowerShell Function: Install-CoraSeSequenceArchiveDatabase

Last Modified on 12/08/2020 2:46 am EST

V9.5

## Module

CoraSeSequence.Database

## Description

Deploys a Cora SeSequence archive database package.

### NOTE

Run this function to deploy Cora SeSequence archive databases only.

## Syntax

```
Install-CoraSeSequenceArchiveDatabase [-DatabasePackagePath] [-SQLServer] [-Database] [[-SQLCredentials] ] [[-Credentials] ] [-Diagnostics] [[-Parameters] ] [[-Properties] ]  
[]
```

## Parameters

### -DatabasePackagePath

The path to the archive database package.

Required?	true
Position?	1
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

### -SQLServer

The name of the SQL server used for hosting the Cora SeSequence archive database. SQL server setup should follow Microsoft SQL standards and, include instance name and port.

Required?	true
Position?	2
Default value	
Accept pipeline input?	false

Accept wildcard characters?	false
-----------------------------	-------

### **-Database**

Determines the name of the deployed archive database.

Required?	true
Position?	3
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

### **-SQLCredentials**

The credentials to be used to connect to the SQL server, if needed. If not provided, the current user credentials are used with Windows Authentication.

Required?	false
Position?	4
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

### **-Credentials**

Credentials used to access **DatabasePackagePath**, if needed.

Required?	false
Position?	5
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

### **-Diagnostics []**

Enables diagnostics for the database deployment. After deployment, a log file is created in the same

location of the deployment files, under a temporary folder.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

### **-Parameters**

Adds additional parameters to the sqlpackage as specified [here](#).

Required?	false
Position?	6
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

### **-Properties**

Adds additional properties to the sqlpackage as specified [here](#).

Required?	false
Position?	7
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

This function supports these common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable.

For more information, see [about\\_CommonParameters](#).

### **Examples**

With credentials:

```
PS C:\>Install-CoraSeQuenceArchiveDatabase -DatabasePackagePath "C:\PNMsoft.Sequence.SqlDatabase.Archiving_9.4.0.0.dacpac" -SQLServer "MySQLServer" -Database "CoraSeQuenceArchive" -SQLCredentials (Get-Credential)
```

## V9.4

### Module

CoraSeQuence.Database

### Description

Deploys a Cora SeQuence archive database package.

#### NOTE

Run this function to deploy Cora SeQuence archive databases only.

### Syntax

```
Install-CoraSeQuenceArchiveDatabase [-DatabasePackagePath] [-SQLServer] [-Database] [[-SQLCredentials] ] [[-Credentials] ] [-Diagnostics] []
```

### Parameters

#### **-DatabasePackagePath**

The path to the archive database package.

Required?	true
Position?	1
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

#### **-SQLServer**

The name of the SQL server used for hosting the Cora SeQuence archive database. SQL server setup should follow Microsoft SQL standards and, include instance name and port.

Required?	true
Position?	2

Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

#### **-Database**

Determines the name of the deployed archive database.

Required?	true
Position?	3
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

#### **-SQLCredentials**

The credentials to be used to connect to the SQL server, if needed. If not provided, the current user is used with Windows Authentication.

Required?	false
Position?	4
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

#### **-Credentials**

The credentials to be used to access **DatabasePackagePath**, if needed.

Required?	false
Position?	5
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

#### **-Diagnostics []**

Enables diagnostics for the database deployment. After deployment, a log file is created in the same location of the deployment files, under a temporary folder.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

This function supports these common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable.

For more information, see [about\\_CommonParameters](#).

## Examples

With credentials:

```
PS C:\>Install-CoraSeQuenceArchiveDatabase -DatabasePackagePath "C:\PNMsoft.Sequence.SqlDatabase.Archiving_9.4.0.0.dacpac" -SQLServer "MySQLServer" -Database "CoraSeQuenceArchive" -SQLCredentials (Get-Credential)
```