

PowerShell Function: Set-CoraSeSequenceBRSThreadConfiguration

Last Modified on 10/26/2022 7:48 am EDT

V9.5

Module

CoraSeSequence.Services

Description

Sets configuration of a Cora SeQuence BRS thread.

Syntax

```
Set-CoraSeSequenceBRSThreadConfiguration [-ServiceID <Int32>] [-Redirector] [-Interval <Int32>] [-PageSize <Int32>] [<CommonParameters>]
```

```
Set-CoraSeSequenceBRSThreadConfiguration [-ServiceID <Int32>] [-EmailSender] [-Interval <Int32>] [-SendRetries <Int32>] [-SiteUrl <Uri>] [<CommonParameters>]
```

```
Set-CoraSeSequenceBRSThreadConfiguration [-ServiceID <Int32>] [-ClosedInstancesSeparator] [-Interval <Int32>] [-PageSize <Int32>] [-StartAt <String>] [-StopAt <String>] [<CommonParameters>]
```

Parameters

-ServiceID <Int32>

The numeric ID of the BRS service instance. If not provided, the configuration is applied to all BRS instances deployed on the server.

Required?	false
Position?	named
Default value	0
Accept pipeline input?	false
Accept wildcard characters?	false

-Redirector [<SwitchParameter>]

Switch to configure the Redirector thread.

Required?	false
Position?	named

Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-EmailSender [<SwitchParameter>]

Switch to configure the Emailsender thread.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-ClosedInstancesSeparator [<SwitchParameter>]

Switch to configure the ClosedInstancesSeparator thread.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-Interval <Int32>

Interval (in minutes) to configure for the specified thread.

Required?	false
Position?	named
Default value	0

Accept pipeline input?	false
Accept wildcard characters?	false

-PageSize <Int32>

Page size to configure the Redirector and ClosedInstancesSeparator threads.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-SendRetries <Int32>

Number of retries when email sending fails. This is valid for EmailSender thread.

Required?	false
Position?	named
Default value	0
Accept pipeline input?	false
Accept wildcard characters?	false

-SiteUrl <Uri>

Flowtime site URL for EmailSender thread.

Required?	false
Position?	named
Default value	
Accept pipeline input?	false

Accept wildcard characters?	false
-----------------------------	-------

-StartAt <String>

Start hour in hh:mm format when ClosedInstancesSeparator thread is active.

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-StopAt <String>

Stop hour in hh:mm format when ClosedInstancesSeparator thread is active.

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

<CommonParameters>

This command supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable.

For more information, see [about_CommonParameters](#).

Example

```
PS C:\>Set-CoraSeQuenceBRSThreadConfiguration -EmailSender -Interval 5 -SendRetries 3 -SiteUrl "https://myflowtime.mycorp.com/_layouts/"
```

```
PS C:\>Set-CoraSeQuenceBRSThreadConfiguration -ServiceID 2 -Redirector -Interval 1 -PageSize 100
```