

# PowerShell Function: Set-CoraSeQuenceBRSThreadConfiguration

Last Modified on 12/08/2020 4:39 am EST

V9.5

Module

CoraSeQuence.Services

## Description

Sets configuration of a Cora SeQuence BRS thread.

## Syntax

```
Set-CoraSeQuenceBRSThreadConfiguration [-ServiceID ] [-Redirector] [-Interval ] [-PageSize ] []
```

```
Set-CoraSeQuenceBRSThreadConfiguration [-ServiceID ] [-EmailSender] [-Interval ] [-SendRetries ] [ -SiteUrl ] []
```

```
Set-CoraSeQuenceBRSThreadConfiguration [-ServiceID ] [-ClosedInstancesSeparator] [-Interval ] [-P ageSize ] [-StartAt ] [-StopAt ] []
```

## Parameters

### -ServiceID

The numeric ID of the BRS service instance. If not provided, the configuration is applied to all BRS instances deployed on the server.

Required?	false
Position?	named
Default value	0
Accept pipeline input?	false
Accept wildcard characters?	false

### -Redirector []

Switch to configure the Redirector thread.

Required?	false
Position?	named
Default value	False

Accept pipeline input?	false
Accept wildcard characters?	false

### **-EmailSender []**

Switch to configure the Emailsender thread.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

### **-ClosedInstancesSeparator []**

Switch to configure the ClosedInstancesSeparator thread.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

### **-Interval**

Interval (in minutes) to configure for the specified thread.

Required?	false
Position?	named
Default value	0
Accept pipeline input?	false

Accept wildcard characters?	false
-----------------------------	-------

### **-PageSize**

Page size to configure the Redirector and ClosedInstancesSeparator threads.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

### **-SendRetries**

Number of retries when email sending fails. This is valid for EmailSender thread.

Required?	false
Position?	named
Default value	0
Accept pipeline input?	false
Accept wildcard characters?	false

### **-SiteUrl**

Flowtime site URL for EmailSender thread.

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

### **-StartAt**

Start hour in hh:mm format when ClosedInstancesSeparator thread is active.

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

### **-StopAt**

Stop hour in hh:mm format when ClosedInstancesSeparator thread is active.

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

This command supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable.

For more information, see [about\\_CommonParameters](#).

### **Example**

```
PS C:\>Set-CoraSeQuenceBRSThreadConfiguration -EmailSender -Interval 5 -SendRetries 3 -SiteUrl "https://myflowtime.mycorp.com"
```

```
PS C:\>Set-CoraSeQuenceBRSThreadConfiguration -ServiceID 2 -Redirector -Interval 1 -PageSize 100
```