

Cora SeSequence predefined configurations

Last Modified on 03/23/2021 11:23 am EDT

V9.6 and later

The predefined configurations come packaged with the Cora SeSequence applications as part of the deployment.

Standard configurations

| Configuration name | Valid for |
|-------------------------------|-----------------------------|
| AddFilesStorageConnection | All applications |
| AzureKeyVault | All applications |
| CORS | WebAPI |
| DefaultFilesStorageConnection | All applications |
| EnableLogging | All applications |
| FormsAuthentication | Administration and Flowtime |
| HTTP | All sites |
| HTTPS | All sites |
| MachineKey | All sites |
| OAuth | WebAPI |
| OpenIDConnect | Administration and Flowtime |
| QuickSearch | Flowtime (Premium only) |
| SAML | Administration and Flowtime |
| Windows Authentication | All sites |

AddFilesStorageConnection

| Token | Description | Expected value |
|---------------------------|-----------------------------------|--|
| SEQ_StorageConnectionName | A name for the storage connection | Any string, except <i>CoraSeSequence.Default</i> |

| Token | Description | Expected value |
|---------------------------|------------------------|---|
| SEQ_StorageConnectionType | The type of connection | <ul style="list-style-type: none"> • AzureFileStorage • AzureBlobStorage • FTP • SFTP • NetworkStorage |
| SEQ_StorageRelativePath | The relative path | - |
| SEQ_StorageConnection | Connection details | - |

AzureKeyVault

| Token | Description | Expected value |
|------------|-------------|----------------|
| ENV_PREFIX | - | - |

CORS

| Token | Description | Expected value |
|-------------------|---------------------------------|---|
| SEQ_IsCORSEnabled | Defines whether CORS is enabled | <ul style="list-style-type: none"> • True • False |

DefaultFileStorageConnection

| Token | Description | Expected value |
|------------------------|---|---|
| SEQ_DefaultStorageName | The default storage connection name from the list of available configurations | A valid connection name that has been defined as a file storage connection or <i>CoraSeSequence.Default</i> for using the main database for file storage. |

EnableLogging

| Token | Description | Expected value |
|-------------------|---|--|
| SEQ_LogSourceName | The Cora SeSequence log source to enable | sequence.runtime, sequence.host, sequence.jobs (JES only) |
| SEQ_LogSwitchName | The Cora SeSequence log source switch to enable | sequence.runtime.switch, sequence.host.switch, sequence.jobs.switch (JES only) |

| Token | Description | Expected value |
|---------------------|------------------------------------|--|
| SEQ_ApplicationType | The Cora SeQuence application type | Administration, ADSS, BRS, Flowtime, JES, WebAPI |
| SEQ_TraceDirectory | The path to store the logs | The valid local path where the application user writes permissions |

HTTP and HTTPS

| Token | Description | Expected value |
|-----------------|--|----------------|
| SEQ_Application | <p>A name to represent the application. The name does not have to match the application type and is used for cookie configuration only.</p> <div style="border: 1px solid #add8e6; padding: 5px; background-color: #e6f2ff;"> <p>NOTE You need to add a different value for each instance of a site on the same machine.</p> </div> | Any string |

MachineKey

| Token | Description | Expected value |
|-----------------------------|-----------------------------------|--|
| SEQ_MachineKeyDecryption | The machine key decryption method | AES, 3DES, DES |
| SEQ_MachineKeyDecryptionKey | The machine key decryption key | Per IIS allowed values |
| SEQ_MachineKeyValidation | The machine key validation method | AES, MD5, SHA1, 3DES, HMACSHA256, HMACSHA384, HMACSHA512 |
| SEQ_MachineKeyValidationKey | The machine key validation key | Per IIS allowed values |

OAuth

| Token | Description | Expected value |
|--------------------|---|---|
| SEQ_OriginalIssuer | The claims token issuer | Any string |
| SEQ_DiscoveryKind | The method for Cora SeQuence to obtain the public certificate | OpenIdDiscoveryDocument, JsonWebKeySet, Federation, Store |

| Token | Description | Expected value |
|------------------|------------------------------------|----------------|
| SEQ_Authority | The OAuth token endpoint | - |
| SEQ_DiscoveryUri | OpenIDConnect server discovery URI | - |

OpenIDConnect

| Token | Description | Expected value |
|--------------------|---|----------------|
| SEQ_OriginalIssuer | The claims token issuer | Any string |
| SEQ_DiscoveryUri | OpenIDConnect server discovery URI | - |
| SEQ_ClientId | The ID of the application on your IDP | - |
| SEQ_ClientSecret | The secret used to access the application on your IDP | - |

QuickSearch

| Token | Description | Expected value |
|-------------------------|--|--|
| SEQ_QuickSearchEnabled | Defines whether the QuickSearch is enabled | <ul style="list-style-type: none"> • True • False |
| SEQ_QuickSearchPageSize | Returns the page size | <ul style="list-style-type: none"> • Positive number • 0 |

SAML

| Token | Description | Expected value |
|----------------------------|---|----------------|
| SEQ_OriginalIssuer | The claims token issuer | Any string |
| SEQ_AudienceUri | The base URL of the Cora SeQUENCE site | - |
| SEQ_SingleSignOnServiceUrl | The single sign-on URL of the identity provider | - |
| SEQ_SingleLogoutServiceUrl | The single logout URL of the identity provider | - |

WindowsAuthentication

No tokens are required.