

Configure Integrating Messaging Mechanism

Last Modified on 10/20/2021 2:53 am EDT

Overview

The integrating messaging mechanism integrates your workflow with other workflows or applications or services. This mechanism integrates Cora SeQuence with the default internal queue to connect and send information between applications and services.

Install the internal queue (currently Apache ActiveMQ) with Cora SeQuence to use the integrating messaging mechanism. Once installed, use the PowerShell function to set up the connection string for all applications. For PowerShell function parameters, see below.


NOTE

We do not support SQL Service Broker so, Install ActiveMQ to use the integrating messaging mechanism.

The integrating messaging mechanism enables the system to start or resume processes. For example, you can set up a message bus activity for an inter-bank transfer that requires customer's approval based on specific conditions. The message bus sends a message to a queue and Cora SeQuence creates a process for the bank's representative to receive the customer's approval in writing.

With integrating messaging mechanism, the system can trigger multiple processes with one message from the queue.

You can configure the integrating messaging mechanism, under the sequence.engine node in the web.config file.



Or

Use the [PowerShell Function: Set-CoraSeQuenceApplicationConfiguration](#) with the following parameters and values:

```
Set-CoraSeQuenceApplicationConfiguration -ApplicationType Administration -ConfigurationName MessageBusActiveMQ  
-TokensValues @"{"SEQ_ActiveMQConnectionString" = "Server=failover:(tcp://192.168.40.4:61616);Username=admin;  
Password=admin"}" -Verbose
```

The integrating messaging mechanism uses two activities, to listen to messages and start or resume a workflow and to publish the messages to the queue.

- Message Bus producer: to send messages to the internal queue from within workflows.

- Message Bus listener: a JES job to get messages from the internal queue from within workflows.

The Integrating messaging can currently work with two types of entities:

- **Queues:** one direction communication — one sender to one receiver. The message delivery follows a first in, first out (FIFO) method. That is, messages are received and processed in the same order in which they enter the queue. The message bus processes only one message at a time.
- **Topics:** one direction communication — one sender to several receivers, through topics. Messages are sent to a topic and delivered to one or more subscribers. The receiver does not communicate with the topic. Use topics if your activity requires sending messages to several receivers.

Messaging profiles

There are four out-of-the-box messaging profiles available to be mapped to the pipelines. These profiles define how messages will be sent in a queue or a topic.

- **Queue - At Least Once Delivery Guarantee:** using a queue mechanism for a one-to-one communication with a guarantee that the message delivers at least once. This option might cause a message to be delivered multiple times in order to guarantee the delivery.
- **Queue - At Most Once Delivery Guarantee:** using a queue mechanism for a one-to-one communication with a guarantee that a message will not be delivered more than once. This option might prevent a message from being delivered at all.
- **Topic - At Least Once Delivery Guarantee:** using a topic mechanism for a one-to-many communication with a guarantee that the message delivers at least once. This option might cause a message to be delivered multiple times in order to guarantee its delivery.
- **Topic - At Most Once Delivery Guarantee:** using a topic mechanism for a one-to-many communication with a guarantee that a message will not be delivered more than one time. This option might cause a message to be not delivered at all.

Define message bus pipelines

As an admin, you can define pipelines for internal queues.

1. In the Administration site, navigate to **Administration > Global Settings > Message Bus Pipelines**.
2. Click **Add**.
3. Add the following details:

The screenshot shows a configuration window titled "Add record to: Message Bus Pipelines". On the left, a sidebar lists various settings, with "Message Bus Pipelines" highlighted in a red box. The main area contains the following fields and controls:

- Name ***: Text input field containing "Loan request".
- Profile Configuration Name ***: Dropdown menu showing "QueueAtLeastOnceDeliveryGuarantee".
- Connection Name ***: Dropdown menu showing "ActiveMQ".
- Destination Name ***: Text input field containing "Loan team".
- Duplicate Detection ***: A checked checkbox.
- Test Connection**: A button located below the Duplicate Detection checkbox.
- Add** and **Cancel**: Buttons at the bottom of the window.

- o Name: Pipeline name.
- o Profile Configuration Name: type of profile to be mapped to this pipeline.
- o Connection Name: ActiveMQ, by default.
- o Destination Name: The topic or queue where messages will be delivered.
- o Duplicate Detection: select the check box to enable detecting duplicate message based on the correlationId.
- o Test Connection: To test the connection.

4. Click **Add**.


Configure the Message Bus Producer activity

Prerequisites

- Have ActiveMQ installed and configured to set up a connection.
- Set up the Message bus namespace, which is a container for entities, such as queues and topics.
- Create a queue or topic, depending on your implementation requirement.

Procedure

1. In the workflow AppStudio, select **Integration > Message Bus Producer**.
2. Double click **Message Bus Producer**.




3. On the Message Bus Producer Properties screen, give a significant name and alias to the activity, and then click **Next**.
4. Select the MessageBus pipeline.
5. Click **Next**.
6. Expand the Message parameter and add the following details:
 - o CorrelationId: string to determine duplicate message. Is mandatory when the pipeline is configured with duplicate detection.
 - o MessageBody: body of the message.
 - o Headers: the key-value.
7. Click **Finish**.

Configure the Message Bus Listener activity

Procedure

1. In the workflow AppStudio, select **Integration > Message Bus Listener**.
2. Double click **Message Bus Listener**.



3. On the Message Bus Listener Activity Properties screen, give a significant name and alias to the activity, and then click **Next**.
4. On the Job tab, set the following:
 - o **Name:** Enter a name to the actual job performed by the Message Bus Listener activity.
 - o **Scaling:** Set the required scaling settings.
For more details, see [this article](#).
 - o **Job is enabled:** Select this option only after you complete the workflow, or if you want to run the job for testing purposes.
5. Click **Next**.
6. On the Command tab, set the following:
 - o **Pipeline:** Select from the list the pipeline for your message bus namespace.
7. Click **Finish**.

Resume a workflow with the Message Bus Listener activity

Setting up the Message Bus Listener activity to resume a workflow requires additional configuration and integration with an external service.

You should have an active instance of Message Bus Listener for the listener to resume workflow.

After you create the Message Bus Listener activity, it waits for a message to arrive to a queue or topic configured for it. If the `Properties` property of the message contains the `JesActivityInstanceId` key with a value that matches an instance of a Message Bus Listener activity, the Job Execution Service picks up the message and resumes the execution of the workflow.

Procedure

1. In the App Studio:

- a. Place the Message Bus Listener activity anywhere in the workflow, except right after Start.
- b. Get the Message Bus Listener activity instance ID using an expression.

Example: `{MessageBusListener}.ActivityInstanceId`

2. In the external service:

- a. Configure a Header in the Message Bus Listener activity to include an item with a key named `JesActivityInstanceId` and the value received in 1 b. to the queue or topic configured in the activity.

NOTE

If the Message Bus Listener activity was already executed, depending on permissions, the activity may be executed again.

Limitations and important notes

- You cannot have two workflows with the same Message Bus Listener activity job definition. If you copy a workflow, you need to redefine the Message Bus Listener job settings.
- Cora SeQUENCE does not support sessions.
- When you copy or create a new version of a workflow that contains the Message Bus Listener activity, you need to delete the Message Bus Listener activity in the new workflow, and then set it up again.