

Application Variables

Last Modified on 07/10/2024 9:42 am EDT

Starting with V10.0, Cora SeSequence has been renamed to Cora Orchestration.

Overview

Following is the list of the application variables available in Cora SeSequence. For these application variables, a key and its value is defined in the Application Variables table on Admin console, and the key is then used in Cora SeSequence expressions.

For details, see the [this article](#).

Different application variables are defined in the system for different settings explained in the below sections.

Organizational settings

| Key | Type | Description | Value | Version |
|---|-----------------|---|--|----------|
| Administration.Instrumentation.ExternalToolName | Text | Enables you to add the name of the third-party tool you want to use to view logs. By default, the EventViewer opens the logs in Cora Orchestration. | Third-party tool name For example, DataDog | 10.3 |
| Administration.Instrumentation.ExternalToolUrl | Text | Enables you to set the URL of the third-party tool you want to use to view logs. | Tool URL (that will open in a new tab in browser) | 10.3 |
| Administration.Organization.Tree.PageSize | Numeric/Integer | Specifies the number of: <ul style="list-style-type: none">Groups displayed by defaultGroups that load when user clicks Load more | <ul style="list-style-type: none">20 (default)0: displays all groups, without "Load more" | 9.0-10.x |
| Administration.Organization.Tree.Visible | Boolean | Hides or shows the organizational structure on the Organization Management page. | <ul style="list-style-type: none">True (default)False | 9.0-10.x |

| Key | Type | Description | Value | Version |
|--|------|--|--------|------------|
| Administration.Ribbon.EnvironmentColor | Text | Enables you to customize the color of the Administration ribbon. For details, see the Differentiate Cora SeQuence environments with color enhancement in the Cora SeQuence 8.6.1 Release Notes . | ed7b87 | 8.6.1-10.x |
| Administration.Ribbon.EnvironmentText | Text | Enables you to add custom text to the Administration ribbon. For details, see the Differentiate Cora SeQuence environments with color enhancement in the Cora SeQuence 8.6.1 Release Notes . | Dev | 8.6.1-10.x |

Background Runtime Service

These application variables determine batch size, number of instances in batches, and the delay after which aborted instances are moved to closed tables.

For details, see [this article](#).

| Key | Type | Description | Value | Version |
|---|------------------|---|---------------|----------|
| BRS.MoveToClosed.AbortedWorkflowInstancesRetentionDelayInDays | Numeric /Integer | Delay in moving aborted instances to closed tables. | 7 (default) | 9.5-10.x |
| BRS.MoveToClosed.BatchSize | Numeric /Integer | Determines the number of instances that are moved in every batch. | 100 (default) | 9.0-10.x |
| BRS.MoveToClosed.NumberOfBatchesInOneCycle | Numeric /Integer | Maximum number of batches that run in a single service cycle run. | 10 (default) | 9.0-10.x |

Job Execution Services (JES)

These variable determine various settings defined through JES.

For details, see [this article](#).

| Key | Type | Description | Value | Version |
|---|-----------------|--|----------|---------|
| JES.EmailSender.DelaySendOfMessagesInQueueBySeconds | Numeric/Integer | Delay the email send out time. NOTE Decimal values are not allowed. | 0-30 sec | 10.5 |

Case management settings

| Key | Type | Description | Value | Version |
|--|-----------------|---|---|---------|
| Portal.HotOperations.TeamMember.MaxSelectionSize | Numeric/Integer | Maximum number of tasks that can be selected for multiple actions to be performed in the Team Members' <i>Cases assigned to me</i> and <i>Cases in queues</i> task lists. | <ul style="list-style-type: none"> • 25 (default) • 200 (maximum) | 10.7 |
| Portal.HotOperations.GroupListWidth | Numeric/Integer | Maximum width of a combo box. | 400px (default) | 10.4 |
| Portal.HotOperations.GroupPathLength | Numeric/Integer | Maximum number of characters that will appear in a drop down. | n (no max limit) | 10.4 |
| Portal.HotOperations.HideDefaultDashboards | Boolean | Hides or shows the default dashboards in the portal. | <ul style="list-style-type: none"> • True (default) - to show the default dashboards • False - to hide the default dashboards | 10.3.1 |

| Key | Type | Description | Value | Version |
|--|-----------------|---|---|------------------|
| Portal.HotOperations.TeamLeader.MaxSelectionSize | Numeric/Integer | Maximum number of tasks that can be selected for multiple actions to be performed in the Team Leader tasks list | <ul style="list-style-type: none"> • 25 (default) • 200 (maximum <i>for V10.7 onwards</i>) • 100 (maximum <i>for versions previous to V10.7</i>) | 10.7, 9.7.2-10.x |
| Portal.HotOperations.OpsManager.MaxSelectionSize | Numeric/Integer | Maximum number of cases that can be selected for multiple actions to be performed in the Operation Manager cases list | <ul style="list-style-type: none"> • 25 (default) • 200 (maximum <i>for V10.7 onwards</i>) • 100 (maximum <i>for versions previous to V10.7</i>) | 10.7, 9.7.2-10.x |
| Portal.HotOperations.Board.ShowBucketNumberOfCases | Boolean | Hides or shows the number of cases per allocation work bucket in the HotOperations Work Allocation Board for Operations Managers. For details, see this article . | <ul style="list-style-type: none"> • True (default) - to show the property • False - to hide the property | 9.2-10.x |
| Portal.HotOperations.Board.ShowBucketCost | Boolean | Hides or shows the Cost Per Person field in the HotOperations Work Allocation Board for Operations Managers. For details, see this article . | <ul style="list-style-type: none"> • True (default) - to show the field • False - to hide the field | 9.2-10.x |

| Key | Type | Description | Value | Version |
|---|---------|--|--|----------|
| Portal.HotOperations.Grid.TileTemplate.OpsManager | Text | Prevents losing any changes made to the tile display templates on system upgrade. For details, see this article . | Path to the file location. For example, the path to the template of the Team Member grid: [rootfolder]\CoraSeSequence\Flowtime\SharedResources\Components\HotOperations\Flowtime\Templates\TeamMember\MYgrid-tile.html | 9.2-10.x |
| Portal.HotOperations.Grid.ExpandedTileTemplate.OpsManager | | | | |
| Portal.HotOperations.Grid.TileTemplate.TeamLeader | | | | |
| Portal.HotOperations.Grid.ExpandedTileTemplate.TeamLeader | | | | |
| Portal.HotOperations.Grid.TileTemplate.TeamMember | | | | |
| Portal.HotOperations.Grid.ExpandedTileTemplate.TeamMember | | | | |
| Portal.HotOperations.TeamMember.SolutionsMenuId | Text | Determines the menu to which the solutions' task list will be added. | Menu Id | 9.2-9.x |
| Portal.HotOperations.TeamMember.DefaultPage | Text | Determines the Team Member's default task list page of a solution under My Tasks. | URL | 9.2-9.x |
| Portal.HotOperations.TeamMember.EnableGroupFilter | Boolean | Enables the Team Filter feature for Team Members, thus allowing them to filter their tasks by team. | <ul style="list-style-type: none"> • True • False | 9.1-10.x |
| Portal.HotOperations.TeamLeader.EnableSetImportance | Boolean | Enables the Team Leaders to change the Task importance. | <ul style="list-style-type: none"> • True • False (default) | 8.7-10.x |
| Portal.HotOperations.TeamMember.EnableSetImportance | Boolean | Enables the Team Members to change the Task importance. | <ul style="list-style-type: none"> • True • False (default) | 8.7-10.x |

| Key | Type | Description | Value | Version |
|--|---------|---|---|----------|
| Portal.HotOperations.Board.BucketTileTemplate.OpsManager | Text | Enables the Operations Manager to customize the data and style that displays to HotOperations users by modifying <code>default.html</code> file. For details, see this article . | ~/Shared Resources/Components/HotOperations/Flowtime/Templates/OpsManager/default.html (default) | 8.6-10.x |
| Portal.HotOperations.Board.BucketTileTemplate.TeamLeader | Text | Enables the Team Leader to customize the data and style that displays to HotOperations users by modifying <code>default.html</code> file. For details, see this article . | ~/Shared Resources/Components/HotOperations/Flowtime/Templates/TeamLeader/default.html (default) | 8.6-10.x |
| Portal.HotOperations.Board.ShowBucketCost | Boolean | Hides or shows the Cost Per Person in the HotOperations Work Allocation board for Operations Managers. For details, see this article . | <ul style="list-style-type: none"> • True (default) - to show this property • False - to hide this property | 8.7-10.x |
| Portal.HotOperations.Board.ShowBucketUtilization | Boolean | Hides or shows the Workload in the HotOperations Work Allocation board for Operations Managers. For details, see this article . | <ul style="list-style-type: none"> • True (default) - to show this property • False - to hide this property | 8.7-10.x |
| Portal.HotOperations.Board.TeamLeader.DefaultView | Text | Enables focused view for Team Leader Dashboard | <ul style="list-style-type: none"> • All • Focused | 8.6-10.x |
| Portal.HotOperations.OpsManager.DefaultPage | Text | Enables the Operations Manager to set the HotOperations default page to a custom page of their choice. For details, see this article . | ~/HotOperations/OpsManager/CasesList.aspx | 8.6-9.x |

| Key | Type | Description | Value | Version |
|---|------|---|---|---------|
| Portal.HotOperations.TeamLeader.DefaultPage | Text | Enables the Team Leader to set the HotOperations default page to a custom page of their choice. For details, see this article . | ~/HotOperations/OperationsManager/TaskList.aspx | 8.6-9.x |

Portal settings

| Key | Type | Description | Value | Version |
|--|-----------------|---|--|---------|
| Portal.Components.Grid.MaxSelectionSize | Numeric/Integer | Maximum number of tasks that can be selected for multiple actions to be performed in the portal process grids, notifications list and tasks list. | <ul style="list-style-type: none"> • 25 (default) • 200 (maximum) | 10.7 |
| Forms.Controls.FileUploadMaxSizeBytes | Numeric/Integer | Enables the user to check the max file size allowed to be uploaded. This limit is checked after the file is selected and before the file upload is started by the form controls FileUpload, AsyncFileUpload, AttachmentsView. | <ul style="list-style-type: none"> • n • 20,480,000 (20 MB) (default) <p>If value is 0 or (blank), then the upload file size is unlimited.</p> | 10.6 |
| Portal.Components.ShowRecentWorkItems | Boolean | Enables the user to search and view recent work items in the portal, and search a case with case title. | <ul style="list-style-type: none"> • True (default) • False | 10.6 |
| Portal.Components.Grid.DefaultOpenAction | Text | Sets the operation to be performed on clicking a task in a grid. | <ul style="list-style-type: none"> • OpenAndFetch (default) • Open | 10.5 |
| Portal.DefaultProcessPageGuid | Text | Sets the sub menu that correlates to the workflow space guid as the default process page. | WorkflowSpace guid | 10.5 |

| Key | Type | Description | Value | Version |
|---|-----------------|---|---|---------|
| Portal.Forms.Topbar.ShowMenu | Boolean | Enables the user to hide or show the vertical ellipsis menu from the top bar of the case details page | <ul style="list-style-type: none"> • True (default) • False | 10.5 |
| Portal.Substitution | Boolean | Enables substitution functionality for users to set substitute user(s) for themselves. | <ul style="list-style-type: none"> • True • False (default) | 10.4.1 |
| Portal.Substitution.Roles | Text | Sets the roles, members of which can add and enable substitute users for other members of their team. | List of roles Default is Group Manager, Team Leader. | 10.4.1 |
| Portal.Components.Grid.AutoRefreshTime | Numeric/Integer | Number of minutes after which the portal grids will auto refresh. | 1 minute (default) | 10.4 |
| Portal.DefaultSolutionName | Text | Sets the default solution that will appear when user signs in to the portal. | Solution name | 10.3.1 |
| Portal.HideCoraOrchestrationSolution | Boolean | Hides or shows the CoraOrchestration solution from the solution list in the portal. | <ul style="list-style-type: none"> • True - to show the CoraOrchestration solution in the list • False (default) - to hide the CoraOrchestration solution | 10.3.1 |
| Portal.Azure.ApplicationInsights.InstrumentationKey | Text | Enables the user to connect to and use Azure Application Insights. | Instrumentation Key | 10.3 |
| Portal.Components.Grid.PageSize | Numeric/Integer | Enables the user to enter the full-screen mode in the portal to maximize the page view. | <ul style="list-style-type: none"> • 50 (default) | 10.3 |

| Key | Type | Description | Value | Version |
|---|-----------------|--|---|----------|
| Portal.Forms.Conversations.IsModal | Boolean | Enables the user to access the case in the background. | <ul style="list-style-type: none"> • True • False | 10.3 |
| Portal.Components.Workflows.Categories | Boolean | Displays the categories on workflows page | <ul style="list-style-type: none"> • True (default) • False | 10.2 |
| Portal.Navigation.LastLocation | Boolean | Enables the user to land in the portal on the same page where they left in their previous session. | <ul style="list-style-type: none"> • True (default) • False | 10.2 |
| Portal.Components.ToastNotifications.Duration | Numeric/Integer | Number of seconds for which the toast notification will last. | <ul style="list-style-type: none"> • 4 sec (default) | 10.2 |
| Portal.Session.SessionWarningCountdownTime | Numeric/Integer | Displays the session timeout warning in the set number of minutes before session timeout. | <ul style="list-style-type: none"> • n minutes | 10.2 |
| Portal.Links.ContactUs | Text | Adds Contact Us link to Flowtime | <ul style="list-style-type: none"> • URL of an external page • path to Contact Us page in Cora Sequence ~/SequenceForms/wf/WF Space/WFName/FormName/ViewName.ascx | 9.6-10.x |

| Key | Type | Description | Value | Version |
|----------------------------|------|--------------------------------------|--|----------|
| Portal.Links.PrivacyPolicy | Text | Adds Privacy Policy link to Flowtime | <ul style="list-style-type: none"> • URL of an external page • Path to Privacy Policy page in Cora Sequence ~/SequenceForms/wf/WFSpace/WFName/FormName/ViewName.ascx | 9.6-10.x |

Grid settings

Set the path to the customized tile view.

| Key | Type | Description | Value | Version |
|--|------|---|---|----------|
| Portal.Grid.TileTemplate.SearchResults | Text | Indicates the path to the custom layout of a collapsed/expanded tile in the search results grid. For details, see this article . | Path to the file location. For example, the path to the template of the Team Member grid: [rootfolder]\Cora Sequence\Flowtime\Shared Resources\Components\HotOperations\Flowtime\Templates\TeamMember\Mygrid-tile.html | 9.2-10.x |
| Portal.Grid.ExpandedTileTemplate.SearchResults | | | | |

| Key | Type | Description | Value | Version |
|--|------|---|--|----------|
| Portal.Grid.TileTemplate.ProcessTasks | Text | Indicates the path to the custom layout of a collapsed/expanded tile in the tasks page. For details, see this article . | Path to the file location. For example, the path to the template of the Team Member grid: [rootfolder]\Cora SeQuence\Flowtime \Shared Resources\Compon ents\HotOperations \Flowtime\Templat es\TeamMember\M Ygrid-tile.html | 9.2-10.x |
| Portal.Grid.ExpandedTileTemplate .ProcessTasks | | | | |
| Portal.Grid.TileTemplate.ProcessInstances | Text | Indicates the path to the custom layout of a collapsed/expanded tile in the process page tile view. NOTE For V10.x: Go to All Cases > Select a specific workflow template > Select tile view | Path to the file location | 9.2-10.x |
| Portal.Grid.ExpandedTileTemplate .ProcessInstances | | | | |
| Portal.Grid.TileTemplate.UserInstances | Text | Indicates the path to the custom layout of a collapsed/expanded tile in the Cases I Started page tile view. | Path to the file location | 9.2-10.x |
| Portal.Grid.ExpandedTileTemplate .UserInstances | | | | |

[Archive database](#)

Initiate purging of the marked personal data while archiving.

| Key | Type | Description | Value | Version |
|-----|------|-------------|-------|---------|
|-----|------|-------------|-------|---------|

| Key | Type | Description | Value | Version |
|---------------------------------------|---------|---|--|---------|
| JES.Archiving.PurgePiiDuringArchiving | Boolean | Initiates column purging of the marked personal data. For details, see this article . | <ul style="list-style-type: none">• False: default, moves the personal data to the archive database.• True: purges all the personal data columns while moving them to the archive database. | 9.7-9.x |