Application Variables

Last Modified on 10/23/2025 9:23 am EDT

Starting with V10.0, Cora SeQuence has been renamed to Cora Orchestration.

Overview

Following is the list of the application variables available in Cora SeQuence. For these application variables, a key and its value is defined in the Application Variables table on Admin console, and the key is then used in Cora SeQuence expressions.

For details, see the this article.

Different application variables are defined in the system for different settings explained in the below sections.

All workflow execution engines

| Key | Туре | Description | Value | Version |
|---|---------|---|--|---------|
| System.Persistence.ForceDefault Mode | Boolean | Forces the default persistence mode regardless of the workflow configuration. | TrueFalse (default) | 10.8 |

Organizational settings

| - | | | | | | |
|--|------|---|---|---------|--|--|
| Key | Туре | Description | Value | Version | | |
| Administration.Instrumentation.E xternalToolName | Text | Enables you to add the name of the third-party tool you want to use to view logs. By default, the EventViewer opens the logs in Cora Orchestration. | Third-party tool name For example, DataDog | 10.3 | | |
| Administration.Instrumentation.E xternalToolUrl | Text | Enables you to set the URL of the third-party tool you want to use to view logs. | Tool URL (that will open in a new tab in browser) | 10.3 | | |

| Key | Туре | Description | Value | Version |
|--|-------------------------|---|---|----------------|
| Administration.Organization.Tree .PageSize | Numeri c/Integ er | Specifies the number of: • Groups displayed by default. • Groups that load when user clicks Load more. | 20 (default) 0: displays all groups, without "Load more" | 9.0–10.x |
| Administration.Organization.Tree .Visible | Boolea n | Hides or shows the organizational structure on the Organization Management page. | True (default)False | 9.0–10.x |
| Administration.Ribbon.Environm entColor | Text | Enables you to customize the color of the Administration ribbon. For details, see the Differentiate Cora SeQuence environments with color enhancement in the Cora SeQuence 8.6.1 Release Notes. | ed7b87 | 8.6.1– 10.x |
| Administration.Ribbon.Environm entText | Text | Enables you to add custom text to the Administration ribbon. For details, see the Differentiate Cora SeQuence environments with color enhancement in the Cora SeQuence 8.6.1 Release Notes. | Dev | 8.6.1– 10.x |

Background Runtime Service

These application variables determine batch size, number of instances in batches, and the delay after which aborted instances are moved to closed tables.

For details, see this article.

| Key | Туре | Description | Value | Version |
|---|-------------------------|---|---------------|----------|
| BRS.MoveToClosed.AbortedWorkflowInstancesRetentionDelayInDays | Numeri c/Intege r | Delay in moving aborted instances to closed tables. | 7 (default) | 9.5–10.x |
| BRS.MoveToClosed.BatchSize | Numeri c/Intege r | Determines the number of instances that are moved in every batch. | 100 (default) | 9.0–10.x |
| BRS.MoveToClosed.NumberOfB atchesInOneCycle | Numeri c/Intege r | Maximum number of batches that run in a single service cycle run. | 10 (default) | 9.0–10.x |

Job Execution Services (JES)

These variable determine various settings defined through JES. For details, see this article.

| Key | Туре | Description | Value | Version |
|---|-------------------------|---|----------|---------|
| JES.EmailSender.DelaySendOfM essagesInQueueBySeconds | Numeri c/Intege r | Delay the email send out time. NOTE Decimal values are not allowed. | 0-30 sec | 10.5 |

Case management settings

| Key | Туре | Description | Value | Version |
|---|-------------|--|---|---------|
| Portal.Forms.Conversations.Hid eOptionCancelSend | Boolea n | Hides or shows the "Cancel Send" option, in the Conversations, for items in status "in queue". | False (default): Shows the option. True: Hides the option. | 10.7.2 |

| Key | Туре | Description | Value | Version |
|--|-------------------------|---|--|-------------------------|
| Portal.HotOperations.TeamMem ber.MaxSelectionSize | Numeri c/Integ er | Maximum number of tasks that can be selected for multiple actions to be performed in the Team Members' Cases assigned to me and Cases in queues task lists. | 25 (default)200 (maximum) | 10.7 |
| Portal.HotOperations.GroupList Width | Numeri c/Integ er | Maximum width of a combo box. | 400px (default) | 10.4 |
| Portal.HotOperations.GroupPat hLength | Numeri c/Integ er | Maximum number of characters that will appear in a drop down. | n (no max limit) | 10.4 |
| Portal.HotOperations.HideDefau ltDashboards | Boolea n | Hides or shows the default dashboards in the portal. | True - to hide the default dashboards. False (default) - to show the default dashboards. | 10.3.1 |
| Portal.HotOperations.TeamLead er.MaxSelectionSize | Numeri c/Integ er | Maximum number of tasks that can be selected for multiple actions to be performed in the Team Leader tasks list. | 25 (default) 200 (maximum for V10.7 onwards) 100 (maximum for versions previous to V10.7) | 10.7, 9.7.2– 10.x |

| Кеу | Туре | Description | Value | Version | |
|--|-------------------------|--|--|---|----------|
| Portal.HotOperations.OpsManag er.MaxSelectionSize | Numeri c/Integ er | Maximum number of cases that can be selected for multiple actions to be performed in the Operation Manager cases list. | 25 (default) 200 (maximum for V10.7 onwards) 100 (maximum for versions previous to V10.7) | 10.7, 9.7.2– 10.x | |
| Portal.HotOperations.Board.Sho wBucketNumberOfCases | Boolea n | Hides or shows the number of cases per allocation work bucket in the HotOperations Work Allocation Board for Operations Managers. For details, see this article. | True (default) to show the property. False - to hide the property. | 9.2-10.x | |
| Portal.HotOperations.Board.Sho wBucketCost | Boolea n | Hides or shows the Cost Per Person field in the HotOperations Work Allocation Board for Operations Managers. For details, see this article. | True (default) to show the field. False - to hide the field. | 9.2–10.x | |
| Portal.HotOperations.Grid.TileTe mplate.OpsManager Portal.HotOperations.Grid.Expa ndedTileTemplate.OpsManager Portal.HotOperations.Grid.TileTe mplate.TeamLeader Portal.HotOperations.Grid.Expa | Text | Text | Prevents losing any changes made to the tile display templates on system upgrade. For details, see this article. | Path to the file location. For example, the path to the template of the Team Member grid: [rootfolder]\Cora SeQuence\Flowtim e\Shared | 9.2–10.x |
| ndedTileTemplate.TeamLeader Portal.HotOperations.Grid.TileTe mplate.TeamMember Portal.HotOperations.Grid.Expa ndedTileTemplate.TeamMember | | | Resources\Compon ents\HotOperation s\Flowtime\Templa tes\TeamMember\ MYgrid-tile.html | | |

| Key | Туре | Description | Value | Version |
|--|-------------|---|--|----------|
| Portal.HotOperations.TeamMem ber.SolutionsMenuId | Text | Determines the menu to which the solutions' task list will be added. | Menu Id | 9.2-9.x |
| Portal.HotOperations.TeamMem ber.DefaultPage | Text | Determines the Team Member's default task list page of a solution under My Tasks. | URL | 9.2-9.x |
| Portal.HotOperations.TeamMem ber.EnableGroupFilter | Boolea n | Enables the Team Filter feature for Team Members, thus allowing them to filter their tasks by team. | TrueFalse | 9.1–10.x |
| Portal.HotOperations.TeamLead er.EnableSetImportance | Boolea n | Enables the Team Leaders to change the Task importance. | TrueFalse (default) | 8.7–10.x |
| Portal.HotOperations.TeamMem ber.EnableSetImportance | Boolea n | Enables the Team Members to change the Task importance. | TrueFalse (default) | 8.7–10.x |
| Portal.HotOperations.Board.Buc ketTileTemplate.OpsManager | Text | Enables the Operations Manager to customize the data and style that displays to HotOperations users by modifying default.htm file. For details, see this article. | ~/Shared Resources/Compon ents/HotOperation s/Flowtime/Templa tes/OpsManager/d efault.html (default) | 8.6-10.x |
| Portal.HotOperations.Board.Buc ketTileTemplate.TeamLeader | Text | Enables the Team Leader to customize the data and style that displays to HotOperations users by modifying default.htm file. For details, see this article. | ~/Shared Resources/Compon ents/HotOperation s/Flowtime/Templa tes/TeamLeader/de fault.html (default) | 8.6–10.x |

| Key | Туре | Description | Value | Version |
|---|-------------|---|--|----------|
| Portal.HotOperations.Board.Sho wBucketCost | Boolea n | Hides or shows the Cost Per Person in the HotOperations Work Allocation board for Operations Managers. For details, see this article. | True (default) to show this property. False - to hide this property. | 8.7–10.x |
| Portal.HotOperations.Board.Sho wBucketUtilization | Boolea n | Hides or shows the Workload in the HotOperations Work Allocation board for Operations Managers. For details, see this article. | True (default) to show this property. False - to hide this property. | 8.7–10.x |
| Portal.HotOperations.Board.Tea mLeader.DefaultView | Text | Enables focused view for Team Leader Dashboard. | All Focused | 8.6–10.x |
| Portal.HotOperations.OpsManag er.DefaultPage | Text | Enables the Operations Manager to set the HotOperations default page to a custom page of their choice. For details, see this article. | ~/HotOperations/O psManager/CasesLi st.aspx | 8.6-9.x |
| Portal.HotOperations.TeamLead er.DefaultPage | Text | Enables the Team Leader to set the HotOperations default page to a custom page of their choice. For details, see this article. | ~/HotOperations/O psManager/TaskLis t.aspx | 8.6-9.x |

Portal settings

| 1 | e Descrip | otion Value | Version |
|---|-----------|-------------|---------|
|---|-----------|-------------|---------|

| Key | Туре | Description | Value | Version |
|--|-------------------------|---|--|---------|
| Portal.Components.Grid.MaxSel ectionSize | Nume ric/Int eger | Maximum number of tasks that can be selected for multiple actions to be performed in the portal process grids, notifications list and tasks list. | 25 (default)200 (maximum) | 10.7 |
| Forms.Controls.FileUploadMaxSi zeBytes | Nume ric/Int eger | Enables the user to check the max file size allowed to be uploaded. This limit is checked after the file is selected and before the file upload is started by the form controls FileUpload, AsyncFileUpload, AttachmentsView. | • n • 20,480,000 (20 MB) (default) If yalue is 0 or he unlimited. | 10.6 |
| Portal.Components.ShowRecent WorkItems | Boole an | Enables the user to search and view recent work items in the portal, and search a case with case title. | True (default)False | 10.6 |
| Portal.Components.Grid.Default OpenAction | Text | Sets the operation to be performed on clicking a task in a grid. Is valid for the following grids: Cases assigned to me Cases in Queue My Tasks | OpenAndFet ch (default)Open | 10.5 |
| Portal.DefaultProcessPageGuid | Text | Sets the sub menu that correlates to the workflow space guid as the default process page. | WorkflowSpace guid | 10.5 |
| Portal.Forms.Topbar.ShowMenu | Boole an | Enables the user to hide or show the vertical ellipsis menu from the top bar of the case details page. | True (default)False | 10.5 |

| Key | Туре | Description | Value | Version |
|---|-------------------------|---|---|---------|
| Portal.Substitution | Boole an | Enables substitution functionality for users to set substitute user(s) for themselves. | TrueFalse (default) | 10.4.1 |
| Portal.Substitution.Roles | Text | Sets the roles, members of which can add and enable substitute users for other members of their team. | List of roles Default is Group Manager, Team Leader. | 10.4.1 |
| Portal.Components.Grid.AutoRef reshTime | Nume ric/Int eger | Number of minutes after which the portal grids will auto refresh. | 1 minute (default) | 10.4 |
| Portal.DefaultSolutionName | Text | Sets the default solution that will appear when user signs in to the portal. | Solution name | 10.3.1 |
| Portal.HideCoraOrchestrationSol ution | Boole | Hides or shows the CoraOrchestration solution from the solution list in the portal. | True - to hide the CoraOrchest ration solution. False (default) - to show the CoraOrchest ration solution in the list. | 10.3.1 |
| Portal.Azure.ApplicationInsights.InstrumentationKey | Text | Enables the user to connect to and use Azure Application Insights. | Instrumentation Key | 10.3 |
| Portal.Components.Grid.PageSiz e | Nume ric/Int eger | Enables the user to enter the full-screen mode in the portal to maximize the page view. | • 50 (default) | 10.3 |
| Portal.Forms.Conversations.IsMo dal | Boole an | Enables the user to access the case in the background. | • True • False | 10.3 |

| Key | Туре | Description | Value | Version |
|--|-------------------------|--|---|----------|
| Portal.Components.Workflows.C ategories | Boole an | Displays the categories on workflows page. | True (default)False | 10.2 |
| Portal.Navigation.LastLocation | Boole an | Enables the user to land in the portal on the same page where they left in their previous session. | True (default)False | 10.2 |
| Portal.Components.ToastNotific ations.Duration | Nume ric/Int eger | Number of seconds for which the toast notification will last. | • 4 sec (default) | 10.2 |
| Portal.Session.WarningCountdo wnTime | Nume ric/Int eger | Displays the session timeout warning in the set number of minutes before session timeout. | • n minutes | 10.2 |
| Portal.Links.ContactUs | Text | Adds Contact Us link to Flowtime. | URL of an external page. Path to Contact Us page in Cora SeQuence ~/SequenceForms/wf/WF Space/WFNa me/FormNa me/ViewNa me.ascx | 9.6-10.x |

| Key | Туре | Description | Value | Version |
|----------------------------|------|---------------------------------------|--|----------|
| Portal.Links.PrivacyPolicy | Text | Adds Privacy Policy link to Flowtime. | URL of an external page Path to Privacy Policy page in Cora SeQuence ~/SequenceForms/wf/WF Space/WFNa me/FormNa me/ViewNa me.ascx | 9.6-10.x |

Grid settings

Set the path to the customized tile view.

| Key | Туре | Description | Value | Version |
|--|------|---|---|----------|
| Portal.Grid.TileTemplate.Process Tasks Portal.Grid.ExpandedTileTemplat e.ProcessTasks | Text | Indicates the path to the custom layout of a collapsed/expanded tile in the tasks page. For details, see this article. | Path to the file location. For example, the path to the template of the Team Member grid: [rootfolder]\Cora SeQuence\Flowtim e\Shared Resources\Compo nents\HotOperatio ns\Flowtime\Templ ates\TeamMember \MYgrid-tile.html | 9.2–10.x |
| Portal.Grid.TileTemplate.Processl nstances Portal.Grid.ExpandedTileTemplat e.ProcessInstances | Text | Indicates the path to the custom layout of a collapsed/expanded tile in the process page tile view. NOTE For V10.x: Go to All Cases > Select a specific workflow template > Select tile view | Path to the file location | 9.2-10.x |
| Portal.Grid.TileTemplate.UserInst ances Portal.Grid.ExpandedTileTemplat e.UserInstances | Text | Indicates the path to the custom layout of a collapsed/expanded tile in the Cases I Started page tile view. | Path to the file location | 9.2-10.x |

Archive database

Initiate purging of the marked personal data while archiving.

| Key | Туре | Description | Value | Version |
|-----|------|-------------|-------|---------|
|-----|------|-------------|-------|---------|

| Key | Туре | Description | Value | Version |
|--|---------|--|---|---------|
| JES.Archiving.PurgePiiDuringArc hiving | Boolean | Initiates column purging of the marked personal data. For details, see this article. | False: default, moves the personal data to the archive database. True: purges all the personal data columns while moving them to the archive database. | 9.7–9.x |