

Configure File Writer Activity with OAuth

Last Modified on 04/18/2024 6:41 am EDT

V10.x

Overview

Use the File Writer activity to create, edit, and save a file into the database as part of a workflow. After you create the file, you can access and use its data in other activities.

You can configure File Writer activity with OAuth for authentication. To do so you need to follow the steps below:

1. Configure the web.config.
2. Configure the File Writer credentials.
3. Configure ApplicationId user.

1. Configure the web.config

In the web.config file, make sure you have the following:

- A sectionGroup called `identity` with the following sections:
 - `openIdConnect`
 - `oauth`

```
<section name="AIServices" type="FPMsoft.Sequence.AIServices.Translation.AIServicesConfigurationSection, FPMsoft.Sequence.AIServices.Translation, Version=10.0.0.0, Culture=neutral, PublicKeyToken=0a1a190c1c5dca1" s11000
<sectionGroup name="Identity" type="FPMsoft.Sequence.IdentityModel.Configuration.IdentityConfiguration, FPMsoft.Sequence.IdentityModel.v8, Version=10.0.0.0, Culture=neutral, PublicKeyToken=0a1a190c1c5dca1">
  <section name="OpenIdConnect" type="FPMsoft.Sequence.IdentityModel.OpenIdConnect.Configuration.OpenIdConnectConfigurationSection, FPMsoft.Sequence.IdentityModel.OpenIdConnect, Version=10.0.0.0, Culture=neutral, Public
<section name="Oauth" type="FPMsoft.Sequence.IdentityModel.Configuration.OAuthConfigurationSection, FPMsoft.Sequence.IdentityModel.OAuth, Version=10.0.0.0, Culture=neutral, PublicKeyToken=0a1a190c1c5dca1" />
</sectionGroup>
</configSections>
```

- Authentication configured correctly with following parameters:
 - Email and username.
 - AppId
 - Client identifier (application id, for example 7c374b9e-8feb-469a-b0e5-15fdb23fcb2 in this case).
 - Tenant id (For example aefc6520-97fa-44e4-9c87-250eb7be74e3 in this case).
 - Endpoint (v1 in this case), for example - <https://login.microsoftonline.com/aefc6520-97fa-44e4-9c87-250eb7be74e3/oauth2/token>
 - Scope
 - Custom location with your custom runtime.aspx page copied and renamed to GeneratePDF.aspx (you can name it as you want).

```
<authentication impersonate="false">
  <providers>
    <add type="FPMsoft.Security.ClaimsIdentityAuthenticationProvider, FPMsoft.Sequence.IdentityModel.v8, Version=10.0.0.0, Culture=neutral, PublicKeyToken=0a1a190c1c5dca1" />
  </providers>
  <forms enabled="false" />
  <claims enabled="true" signoutFromSts="false" ssoEnabled="true" loginUrl="~/oidcServices/SignInInitiation" logoutUrl="~/oidcServices/SignOutInitiation" accessDeniedUrl="~/AccessDenied.aspx">
    <identityProviders />
    <identityClaims>
      <add claimType="http://schemas.xmlsoap.org/ws/2005/05/identity/claims/emailaddress" originalIssuer="https://sts.windows.net/aefc6520-97fa-44e4-9c87-250eb7be74e3/"
        authenticationType="http://pmssoft.com/sequence/2008/03/authentication/types/EMAIL" />
      <add claimType="http://schemas.xmlsoap.org/ws/2005/05/identity/claims/name" originalIssuer="https://sts.windows.net/aefc6520-97fa-44e4-9c87-250eb7be74e3/"
        authenticationType="http://pmssoft.com/sequence/2008/03/authentication/types/Username" />
      <add claimType="appid" originalIssuer="https://sts.windows.net/aefc6520-97fa-44e4-9c87-250eb7be74e3/" authenticationType="http://pmssoft.com/sequence/2008/03/authentication/types/Username" />
    </identityClaims>
  </claims>
</authentication>
<identity>
  <openIdConnect discoveryKind="OpenIdDiscoveryDocument" discoveryUrl="https://login.microsoftonline.com/aefc6520-97fa-44e4-9c87-250eb7be74e3/v2.0/.well-known/openid-configuration"
    clientId="7c374b9e-8feb-469a-b0e5-15fdb23fcb2" clientSecret="[redacted]" scope="openid" />
  <oauth enabled="false" discoveryKind="OpenIdDiscoveryDocument" authority="https://login.microsoftonline.com/aefc6520-97fa-44e4-9c87-250eb7be74e3/oauth2/v2.0/token"
    discoveryUrl="https://login.microsoftonline.com/aefc6520-97fa-44e4-9c87-250eb7be74e3/v2.0/.well-known/openid-configuration" validAudience="00000003-0000-0000-c000-000000000000"
    validateAudience="false" validIssuer="https://sts.windows.net/aefc6520-97fa-44e4-9c87-250eb7be74e3/" />
</identity>
</sequence.engine>
<connectionStrings />
<location path="~/Layouts/GeneratePDF.aspx">
  <sequence.engine>
    <authentication impersonate="false">
      <claims ssoEnabled="false" />
    </authentication>
    <identity>
      <oauth enabled="true" />
    </identity>
  </sequence.engine>
</location>
```

- Modules
 - OAuthBearerAuthenticationModule

```

<modules>
  <add name="SequenceModule" type="FPMsoft.Sequence.Web.WorkflowEngineHttpModule, FPMsoft.Sequence.Web, Version=10.0.0.0, Culture=neutral, PublicKeyToken=0a1a190c0e5dca1" />
  <add name="SequenceAuthenticationModule" type="FPMsoft.Sequence.Web.AuthenticationModule, FPMsoft.Sequence.Web, Version=10.0.0.0, Culture=neutral, PublicKeyToken=0a1a190c0e5dca1" preCondition="managedHandler" />
  <add name="SequenceSessionAuthenticationModule" type="FPMsoft.Sequence.Web.SequenceSessionAuthenticationModule, FPMsoft.Sequence.Web, Version=10.0.0.0, Culture=neutral, PublicKeyToken=0a1a190c0e5dca1" preCondition="managedHandler" />
  <add name="OpenIDConnectAuthenticationModule" type="FPMsoft.Sequence.IdentityModel.Services.OpenIDConnectAuthenticationHttpModule, FPMsoft.Sequence.IdentityModel.OpenIDConnect, Version=10.0.0.0, Culture=neutral, PublicKeyToken=0a1a190c0e5dca1" />
  <add name="SequenceFormModule" type="FPMsoft.Sequence.Forms.Web.AspFormHttpModule, FPMsoft.Sequence.Forms, Version=10.0.0.0, Culture=neutral, PublicKeyToken=0a1a190c0e5dca1" />
  <add name="RadDpiModule" preCondition="integratedMode" type="FPMsoft.Rad.Web.UI.RadDpiHttpModule, FPMsoft.Rad.Web.UI, Version=2012.03.1017.0, Culture=neutral, PublicKeyToken=29a1a33e0e3492" />
  <add name="RadDpiModule" preCondition="integratedMode" type="FPMsoft.Rad.Web.UI.RadDpiHttpModule, FPMsoft.Rad.Web.UI, Version=2016.1.113.0, Culture=neutral, PublicKeyToken=29a1a33e0e3492" />
  <add name="TelemetryHttpModule" type="OpenTelemetry.Instrumentation.AspNet.TelemetryHttpModule, OpenTelemetry.Instrumentation.AspNet.TelemetryHttpModule" preCondition="integratedMode,managedHandler" />
  <add name="OAuthBearerAuthenticationModule" type="FPMsoft.Sequence.IdentityModel.Services.BearerTokenAuthenticationModule, FPMsoft.Sequence.IdentityModel.OAuth, Version=10.0.0.0, Culture=neutral, PublicKeyToken=0a1a190c0e5dca1" />
</modules>

```

2. Configure the File Writer credentials

- Configure Custom page name and credentials in the File Properties window.
In custom credentials make sure you have (if you work with same application id in Azure, then it's as above):
 - Client Identifier
 - Client Secret
 - Token
 - Scope

Run As ...

Name *

Client Identifier *

Client Secret *

Token Endpoint *

Scopes *

Authentication Method *

Send credentials using the HTTP Basic authentication scheme
 Send credentials in the body of the request

3. Configure ApplicationId user

Because we have added appid claim in the web.config, the application id will be used for authentication when the File Writer tries to access Cora Orchestration from a url.

NOTE

Make sure the appid user has runtime workflow permissions of the viewer of the form that you want to print.

Edit Employee Details ?

First Name *

E-mail

Last Name *

Calendar

Title

Interface Language

Domain

User Name *

Time Zone

Password

[Change Password](#)

Active

Global Administrator

To run it in the Administration debugger, the user must be an administrator or a developer.

The File Writer activity can now work with OAuth authentication.

NOTE

For PDF generation, in case you don't need input elements in the PDF, it's suggested to use read only form or section.

New Form View

Select a method for creating the form view

Option 1 - Automatic View Generation for Query:


Generate a complete responsive form automatically for a selected query.



Form



Grid




Read Only Form



Section



Grid Section



Read Only Section