PowerShell Function: Get-CoraSeQuenceSite

V9.6

Method

CoraSeQuence.Sites

Description

Gets all the Cora SeQuence sites installed on the server.
The returned type is an IIS Site configuration.
For more information, see this page.

In addition, this function returns a hashtable named *CoraSeQuenceProperties* that contains the following keys:

- **BuildDate**: The date on which the application was built.
- **ApplicationName**: The name of the application (ADSS/BRS/JES/Administration/Flowtime/WebAPI).
- **Version**: The version of the application.
- **ProjectName**: The name of the Visual Studio project on which the application was built.
- **ConfigFilePath**: The path to the `web.config` file.

Syntax

```
Get-CoraSeQuenceSite -SiteType <Object> -AllInstances [<CommonParameters>]
```

```
Get-CoraSeQuenceSite -SiteType <Object> [-SiteID <Int32>] [<CommonParameters>]
```

```
Get-CoraSeQuenceSite [-AllSites] [<CommonParameters>]
```

Parameters

-SiteType <Object>

Determines which Cora SeQuence site to retrieve: Flowtime or Administration. If this parameter is not provided, the function returns both sites.

Required?	true
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-SiteID <Int32>

Sets the numeric ID of the site instance.

Required?	false
Position?	named
Default value	1
Accept pipeline input?	false
Accept wildcard characters?	false

-AllInstances [<SwitchParameter>]

If provided, returns all instances of the site provided in the SiteType parameter.

Required?	true
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

-AllSites [<SwitchParameter>]

If provided, returns all instances of all Cora SeQuence sites.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

<CommonParameters>

This function supports these common parameters: Verbose, Debug, ErrorAction, ErrorVariable,

WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable.

For more information, see about_CommonParameters.

Example

```
PS C:\>Get-CoraSeQuenceSite -AllSites
```

```
PS C:\>Get-CoraSeQuenceSite -SiteType Flowtime -AllInstances
```

V9.3

Method

CoraSeQuence.Sites

Description

Gets all the Cora SeQuence sites installed on the server.
The returned type is an IIS Site configuration.
For more information, see this page.

In addition, this function returns a hashtable named CoraSeQuenceProperties that contains the following keys:

- **BuildDate**: The date on which the application was built.
- **ApplicationName**: The name of the application (ADSS/BRS/JES/Administration/Flowtime/WebAPI).
- **Version**: The version of the application.
- **ProjectName**: The name of the Visual Studio project on which the application was built.
- **ConfigFilePath**: The path to the `web.config` file.

Syntax

```
Get-CoraSeQuenceSite [[-SiteType] <Object>] [<CommonParameters>]
```

Parameters

-SiteType <Object>

Determines which Cora SeQuence site to retrieve: Flowtime or Administration.

If this parameter is not provided, the function returns both sites.

Required?	false
Position?	1
Default value	

Accept pipeline input?	false
Accept wildcard characters?	false

<CommonParameters>

This function supports these common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable,   OutBuffer, PipelineVariable, and OutVariable.

For more information, see about_CommonParameters.

Example

```
PS C:\>Get-CoraSeQuenceSite
```

V9.0

Method

CoraSeQuence.Sites

Description

Gets all the Cora SeQuence sites installed on the server.

Syntax

```
Get-CoraSeQuenceSite [[-SiteType] <Object>] [<CommonParameters>]
```

Parameters

-SiteType <Object>

Determines which Cora SeQuence site to retrieve: Flowtime or Administration.

If this parameter is not provided, the function returns both sites.

Required?	false
Position?	1
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

<CommonParameters>

This function supports these common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable,   OutBuffer, PipelineVariable, and OutVariable.

For more information, see about_CommonParameters.

Example

```
PS C:\>Get-CoraSeQuenceSite
```