

PowerShell Function: Install-CoraSeQUENCESite

Last Modified on 07/16/2024 9:34 am EDT

V9.6

Method

CoraSeQUENCE.Sites

Description

Installs, reinstalls, and upgrades a Cora SeQUENCE site.

Syntax

```
Install-CoraSeQUENCESite [-SourcePath] <String> [[-ServiceAccount] <PSCredential>] [[-DestinationPath] <String>] [-SiteType] <Object> [[-SiteID] <Int32>] [<CommonParameters>]
```

Parameters

-SourcePath <String>

The full local path to the application package.

Required?	true
Position?	1
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-ServiceAccount <PSCredential>

The credentials to be used as the Application Pool identity.

Required?	false
Position?	2
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-DestinationPath <String>

The path where the site files are installed. If not provided, the Cora SeQuence default location is used:

```
C:\inetpub\wwwroot\Cora SeQuence\[Site]
```

If the path is provided, but the site already exists, for example in upgrade scenarios, the new path is ignored, and the current site location is used.

Required?	false
Position?	3
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-SiteType <Object>

Determines which Cora SeQuence site is deployed by the package: Flowtime or Administration.

Required?	true
Position?	4
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-SiteID <Int32>

Sets the numeric ID of the site instance.

Required?	false
Position?	5
Default value	1
Accept pipeline input?	false
Accept wildcard characters?	false

<CommonParameters>

This function supports these common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable.

For more information, see [about_CommonParameters](#).

Example

```
PS C:\> Install-CoraSeQuenceSite -SourcePath "C:\Flowtime.zip" -SiteType Flowtime
```

V9.0

Method

CoraSeQuence.Sites

Description

Installs, reinstalls, and upgrades a Cora SeQuence site.

Syntax

```
Install-CoraSeQuenceSite [-SourcePath] <String> [[-ServiceAccount] <PSCredential>] [[-DestinationPath] <String>] [-SiteType] <Object> [<CommonParameters>]
```

Parameters

-SourcePath <String>

The full local path to the application package.

Required?	true
Position?	1
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-ServiceAccount <PSCredential>

The credentials to be used as the Application Pool identity.

Required?	true
-----------	------

Position?	2
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-DestinationPath <String>

The path where the site files are installed. If not provided, the Cora SeQuence default location is used:

```
C:\inetpub\wwwroot\Cora SeQuence\[Site]
```

If the path is provided, but the site already exists, for example in upgrade scenarios, the new path is ignored, and the current site location is used.

Required?	true
Position?	3
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-SiteType <Object>

Determines which Cora SeQuence site is deployed by the package: Flowtime or Administration.

Required?	true
Position?	1
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

<CommonParameters>

This function supports these common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable.

For more information, see [about_CommonParameters](#).

Example

```
PS C:\> Install-CoraSeQuenceSite -SourcePath "C:\Flowtime.zip" -SiteType Flowtime
```

