

PowerShell Function: Set-CoraSeQUENCESiteAuthentication

Last Modified on 08/01/2024 4:57 am EDT

V9.6

Method

CoraSeQUENCE.Sites

Description

Sets basic authentication types: Forms, Claims, or Windows, for a Cora SeQUENCE site.

Syntax

```
Set-CoraSeQUENCESiteAuthentication [-SiteType] <Object> [-AuthenticationType] <Object> [[-SiteID] <Int32>] [-AllInstances] [<CommonParameters>]
```

Parameters

-SiteType <Object>

Determines which Cora SeQUENCE site the deployed package is: Flowtime or Administration or WebAPI.

Required?	true
Position?	1
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-AuthenticationType <Object>

Defines the authentication type to set: Forms, Windows, or Claims (claims require additional manual configurations).

Required?	true
Position?	2
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-SiteID <Int32>

Sets the numeric ID of the site instance. Ignored if AllInstnaces is used.

Required?	false
Position?	3
Default value	1
Accept pipeline input?	false
Accept wildcard characters?	false

-AllInstances [<SwitchParameter>]

If provided, this parameter applies to all instances of the site provided in the SiteType parameter.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	false
Accept wildcard characters?	false

<CommonParameters>

This function supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable.

For more information, see [about_CommonParameters](#).

Examples

```
PS C:\>Set-CoraSeQuenceSiteAuthentication -SiteType Administration -AuthenticationType Forms
```

```
PS C:\>Set-CoraSeQuenceSiteAuthentication -SiteType Flowtime -AuthenticationType Windows
```

V9.0

Method

Description

Sets basic authentication types: Forms, Claims, or Windows, for a Cora SeQuence site.

Syntax

```
Set-CoraSeQuenceSiteAuthentication [-SiteType] <Object> [-AuthenticationType] <Object> [<CommonParameters>]
```

Parameters

-SiteType <Object>

Determines which Cora SeQuence site the deployed package is: Flowtime or Administration.

Required?	true
Position?	1
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-AuthenticationType <Object>

Defines the authentication type to set: Forms, Windows, or Claims (claims requires additional manual configurations).

Required?	true
Position?	2
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

<CommonParameters>

This function supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable.

For more information, see [about_CommonParameters](#).

Examples

```
PS C:\>Set-CoraSeQuenceSiteAuthentication -SiteType Administration -AuthenticationType Forms
```

```
PS C:\>Set-CoraSeQuenceSiteAuthentication -SiteType Flowtime -AuthenticationType Windows
```