

Configure Workflow Explorer via Config Set

Last Modified on 03/26/2026 6:34 am EDT

Starting with V11.0, Cora Orchestration has been renamed to Orchestration AI.

V11.1

Overview

As a workflow developer, you can configure workflow explorer objects like Form, Task, Dynamic Task, and Message with a config set. The configuration made through config set overrides the configuration made in the `\Shared Resources\Components\WorkflowExplorer\Config\WorkflowExplorer.config` file on the server.

To configure workflow explorer objects with a config set, you need to follow the steps below:

#	Step
1	Define YAML in the config set.
2	Configure app variable.

Define config set for configuring workflow explorer objects

Defining a case config set for workflow explorer objects is similar to creating a generic case config set. For procedure, see [this article](#).

You need to create the following YAML file in the ConfigSet AppStudio.

IMPORTANT

You can name the files anything of your choice, but need to keep the *kind* and *metadata name* exactly as mentioned in the table below.

YAML file	Kind	Metadata name	Command Manager Id
workflow explorer ui	Document	config-set/v1/ui-workflow-explorer	sq.ui.workflowexplorer.ft.portal

Sample ConfigSet YAML file

For configuring workflow explorer objects, download the following sample YAML file:

- [workflow_explorer_ui.yaml](#) 

Configuring app variable

The workflow developer sets the **Portal.UI.ConfigSetId** app variable to load the configuration (if exists)

on page load.
